

cadMIX

Unique 2 in 1 solution
for refreshing SLS powders
and tumbling finished prints



Refreshing

Saves work and time

one operation instead
of three or more when using
classic sieve

Ensures clean process

there is no need for repeated
manipulation, the whole process is
automatic

Mix perfectly

precisely prepared SLS powder
in few minutes

Works completely safely

the whole process takes place in closed
chamber with sensor for immediate stop

Tumbling

Saves work and time

replaces sanding of the prints, and the
associated time requirement of the
process.

Perfect post-process

no part of the print
is left unprocessed.

Allows the choice of abrasive

for use on other materials as well (metal,
wood) depending on the chosen abrasive.

Works completely safely

the whole process takes place in closed
chamber with sensor for immediate stop.

Package dimensions

Height [mm]	80
Width [mm]	45
Depth [mm]	62
Mass [kg]	40

A part of the package



Height [mm]	700
Width [mm]	420
Depth [mm]	575
Mass [kg]	35
Input power [W]	400
Tension [V]	230
Speed range [rpm]	1 - 115



SLS 3D print,
that you
will enjoy

CADMIA 3D, s.r.o., Nádražní 1958/48d, 785 01 Šternberk
info@cadmia3d.cz | www.cadmia3d.cz

CADMIA 3D